

ADVANCE TO *THE NEXT LEVEL* IN TRANSPORTATION

1926 HD INTERCITY CHASSIS


//// TORQSHIFT



BHARAT6+



High Powered
Engine



Globally Proven
AMT



Unitized
Bearing



Glide Air
Suspension



TTPMS
Interface

Engine

Model	OM926 BSVI OBD-II
Maximum Power (kW)	260 HP (191 kW) @ 2200 rpm
Maximum Torque (Nm)	900 Nm @ 1200 - 1600 rpm
No. of Cylinders, cc	6; 7200

Transmission

Gearbox Model & Type	TORQSHIFT, 6F + 1R
Clutch Type	Organic, Single Dry Plate Self Adjusting Clutch
Clutch Diameter	395

Axle

Front Axle	IF7.0
Rear Axle	RS440
Rear Axle Ratio	4.77

Chassis Frame & Suspension

Frame Section (D x W x T) (mm)	241 x 66.5 x 7
Suspension	Pneumatic Suspension with Anti Roll Bar & Shock Absorber at Front & Rear

Brake & Tyre

Service Brake	Dual Circuit, Pneumatic, Drum Type
Parking Brake	Spring Actuated with Hand Control Valve
Auxiliary Brake	Engine Brake with Exhaust Brake
Retarder Brake	ECU Controlled 5-Stage Electromagnetic Retarder as Standard
Tyres Pattern & Size	295/80 R22.5 Radial Tubeless Tyre

Steering

Steering Type	Power Steering, Adjustable & Tiltable
---------------	---------------------------------------

Fuel Tank & Electrical

Fuel Tank / Filling Capacity (L)	380 / 355
AdBlue Tank / Filling Capacity (L)	60 / 50
Voltage (V)	24V
Battery Capacity (Ah)	2x12V, 200Ah

Vehicle Dimension

Wheelbase (mm)	6850
Overall Length (mm)	13196
Overall Width (mm)	2530
Overall Height (mm)	2335
Front Overhang (mm)	2305
Rear Overhang (mm)	4041
Ground Clearance (mm)	239

Weight

Gross Vehicle Weight (kg)	19500
---------------------------	-------